

# 2010 IPHC Stock Assessment Survey

## Area 3B

Station	Date Fished	North Latitude	West Longitude	Depth (F)	Skates Set <sup>1</sup>	Legal Halibut		Sublegal Halibut		Bycatch (numbers) <sup>3</sup>		
						Lbs. <sup>2</sup>	#'s	Lbs. <sup>2</sup>	#'s	Sablefish	P. Cod	Rockfish
5001	6/30	56° 00.02'	-153° 36.20'	51	8.0	1,661	97	1,296	183	0	0	0
5002	6/30	55° 59.98'	-153° 54.04'	68	8.1	370	27	696	114	0	81	0
5003	6/29	56° 00.03'	-154° 13.21'	58	8.1	2,012	118	985	133	0	0	10
5004	6/29	56° 00.20'	-154° 29.61'	255	8.1	161	9	20	2	222	0	10
5005	6/28	55° 59.97'	-154° 47.85'	119	8.1	577	36	343	44	25	61	0
5006	6/28	55° 59.92'	-155° 05.80'	33	8.0	218	15	544	88	0	192	0
5007	6/30	56° 10.02'	-153° 36.00'	81	8.1	434	34	757	101	0	66	0
5008	7/1	56° 10.04'	-153° 53.11'	122	8.0	1,491	102	487	58	69	40	0
5009	7/1	56° 10.05'	-154° 11.24'	63	8.0	719	52	1,176	170	0	20	0
5010	6/29	56° 09.88'	-154° 28.91'	51	8.1	1,531	86	1,141	156	0	25	0
5011	6/28	56° 10.01'	-154° 46.85'	43	8.0	966	63	971	135	0	35	0
5013	6/27	56° 10.09'	-155° 23.41'	19	8.0	790	54	1,167	166	0	70	0
5014	6/27	56° 09.90'	-155° 40.65'	32	8.0	539	28	858	138	0	54	0
5015	7/1	56° 19.88'	-153° 50.98'	48	8.0	693	49	1,148	149	0	10	0
5016	7/2	56° 19.95'	-154° 09.96'	50	8.0	928	60	894	119	0	75	0
5017	7/2	56° 19.95'	-154° 27.82'	34	8.1	449	28	326	43	0	36	0
5018	6/27	56° 19.98'	-155° 22.12'	24	8.0	194	12	1,034	158	0	95	0
5019	6/19	56° 20.01'	-155° 40.16'	39	8.0	526	21	543	97	0	155	0
5020	6/19	56° 30.12'	-155° 21.36'	28	8.0	521	29	707	104	0	175	0
5021	6/19	56° 30.00'	-155° 38.54'	63	8.1	1,399	85	582	74	0	172	0
5022	6/11	56° 40.03'	-155° 01.33'	20	8.1	1,602	77	323	43	0	178	0
5023	6/11	56° 39.66'	-155° 19.51'	46	8.0	931	52	388	50	0	239	0
5024	6/18	56° 40.25'	-155° 39.16'	132	8.0	1,124	72	362	44	30	79	0
5025	6/20	56° 40.09'	-155° 56.35'	158	8.0	331	20	73	9	115	75	0
5026	6/9	56° 50.03'	-154° 24.00'	32	8.1	511	29	450	63	0	268	0
5027	6/9	56° 50.06'	-154° 41.82'	24	8.0	818	55	1,149	158	0	114	0
5028	6/10	56° 50.08'	-155° 00.31'	39	8.0	1,249	70	689	96	0	222	0
5029	6/18	56° 50.04'	-155° 18.42'	122	8.0	820	54	366	45	45	80	5
5030	6/18	56° 49.99'	-155° 36.55'	151	8.0	484	28	105	14	145	70	0
5031	6/20	56° 50.00'	-155° 55.02'	162	8.0	429	21	38	5	168	99	0
5032	6/9	56° 59.97'	-154° 40.48'	20	8.0	1,403	74	635	79	0	180	0
5033	6/10	57° 00.03'	-154° 58.67'	57	8.0	533	38	399	56	0	150	0
5034	6/10	57° 00.01'	-155° 17.96'	136	8.1	845	59	233	26	90	55	0
5035	6/17	56° 59.66'	-155° 35.86'	153	8.0	271	18	75	9	150	130	0
5036	6/17	57° 00.23'	-155° 53.81'	163	8.0	316	18	47	6	135	80	0
5037	6/8	57° 09.99'	-154° 39.79'	28	8.0	983	56	497	70	0	191	0
5038	6/8	57° 10.14'	-154° 59.49'	108	8.1	1,689	111	861	105	0	127	0
5039	6/16	57° 10.16'	-155° 16.41'	134	8.0	698	39	103	12	15	165	0
5040	6/16	57° 10.00'	-155° 35.21'	149	8.0	294	13	55	7	84	99	0
5041	6/15	57° 09.97'	-155° 53.02'	135	8.0	792	43	121	16	55	199	0
5042	6/8	57° 19.91'	-154° 56.71'	99	8.0	807	51	672	83	0	292	0
5043	6/7	57° 20.09'	-155° 15.13'	134	8.0	602	31	82	10	35	159	0
5044	6/16	57° 20.02'	-155° 34.46'	156	8.0	551	33	163	19	111	70	0
5045	6/15	57° 19.81'	-155° 52.02'	56	8.1	847	50	1,356	178	0	61	0
5046	6/15	57° 20.20'	-156° 10.96'	70	8.0	1,148	57	349	42	0	257	0
5047	6/7	57° 30.02'	-155° 14.22'	139	8.1	582	29	61	9	40	182	0
5048	6/7	57° 29.88'	-155° 32.89'	163	8.0	623	39	277	30	45	55	0
5097	6/27	54° 50.02'	-157° 49.70'	90	8.0	357	27	708	97	0	120	0
5098	6/26	55° 00.01'	-157° 15.01'	105	8.0	77	6	528	72	0	170	0

<sup>1</sup> Standard skate = 1,800' groundline with 16/0 circle hooks spaced every 18' on 24"-42" gangions.

<sup>2</sup> Weights are calculated from length-weight tables.

<sup>3</sup> Bycatch numbers extrapolated from 20% subsample.

# 2010 IPHC Stock Assessment Survey

## Area 3B

Station	Date Fished	North Latitude	West Longitude	Depth (F)	Skates Set <sup>1</sup>	Legal Halibut		Sublegal Halibut		Bycatch (numbers) <sup>3</sup>		
						Lbs. <sup>2</sup>	#'s	Lbs. <sup>2</sup>	#'s	Sablefish	P. Cod	Rockfish
5099	6/27	54° 59.81'	-157° 32.03'	53	8.0	969	65	744	88	0	248	25
5100	7/6	55° 00.02'	-157° 50.07'	45	8.0	1,382	70	949	129	0	160	15
5101	7/6	54° 59.65'	-158° 05.99'	73	8.0	406	25	289	44	0	30	0
5102	6/24	55° 10.16'	-156° 22.03'	276	8.0	0	0	0	0	220	0	5
5103	6/24	55° 10.02'	-156° 39.05'	287	8.0	0	0	0	0	175	0	0
5104	6/26	55° 09.95'	-156° 57.02'	86	8.0	700	51	855	112	0	250	0
5105	6/26	55° 09.94'	-157° 14.00'	61	8.0	1,310	86	1,555	231	0	45	0
5106	7/7	55° 10.00'	-157° 32.13'	46	8.0	1,231	67	1,463	195	0	40	0
5107	7/7	55° 09.96'	-157° 49.06'	43	8.0	668	39	762	109	0	280	0
5108	7/5	55° 10.00'	-158° 06.98'	57	8.0	411	25	1,138	180	0	85	0
5109	6/24	55° 19.85'	-156° 39.02'	64	8.0	804	56	573	80	0	265	0
5110	6/25	55° 19.88'	-156° 56.03'	50	8.0	449	28	631	87	0	275	0
5111	6/25	55° 20.01'	-157° 13.88'	48	8.0	301	19	1,046	158	0	130	0
5112	7/7	55° 20.02'	-157° 30.99'	47	8.0	450	26	1,198	194	0	45	0
5113	7/2	55° 19.98'	-157° 49.02'	45	8.0	334	14	823	137	0	65	0
5114	7/5	55° 20.02'	-158° 06.16'	59	8.0	468	30	871	132	0	106	0
5115	7/5	55° 20.00'	-158° 24.05'	80	8.0	733	52	663	86	0	195	0
5116	6/7	55° 30.00'	-156° 37.95'	102	8.0	1,234	79	633	77	60	155	5
5117	6/25	55° 29.85'	-156° 54.99'	48	8.0	1,261	78	1,141	153	0	80	0
5118	6/23	55° 30.02'	-157° 12.99'	47	8.0	810	56	1,460	211	0	20	0
5119	7/13	55° 29.95'	-157° 31.01'	52	8.0	284	14	795	141	0	110	0
5120	7/2	55° 30.00'	-157° 48.16'	53	8.0	285	19	927	152	0	100	0
5121	7/2	55° 30.05'	-158° 05.99'	71	8.0	160	8	255	33	0	54	0
5122	7/4	55° 30.05'	-158° 23.96'	80	8.0	107	8	159	24	5	40	0
5123	6/23	55° 40.01'	-156° 55.14'	48	8.0	456	23	867	146	0	110	0
5124	6/23	55° 39.98'	-157° 12.89'	46	8.0	253	17	552	94	0	90	0
5125	7/13	55° 39.99'	-157° 29.92'	53	8.0	361	26	789	116	0	163	0
5126	7/13	55° 39.89'	-157° 47.98'	74	8.0	463	36	1,007	139	0	205	0
5127	7/1	55° 40.01'	-158° 05.87'	70	8.0	827	54	676	88	0	85	0
5128	7/4	55° 40.00'	-158° 23.04'	72	8.0	728	54	910	115	0	125	0
5129	7/4	55° 39.98'	-158° 41.05'	49	8.0	282	17	879	135	0	200	0
5130	7/14	55° 49.99'	-157° 11.99'	56	8.0	304	21	973	144	0	188	0
5131	7/14	55° 49.98'	-157° 29.96'	56	8.0	105	8	776	117	0	140	0
5132	7/12	55° 49.94'	-157° 47.64'	64	8.0	387	28	980	139	0	120	0
5133	7/1	55° 50.01'	-158° 05.12'	44	8.0	1,557	73	1,314	185	0	5	0
5134	7/1	55° 49.99'	-158° 22.96'	61	8.0	945	55	639	90	0	150	0
5135	7/15	56° 00.06'	-157° 28.95'	61	8.0	827	51	958	137	0	130	0
5136	7/12	55° 59.99'	-157° 47.06'	67	8.0	200	13	496	70	0	149	0
5137	7/12	56° 00.03'	-158° 05.09'	49	8.0	501	28	564	84	0	140	0
5138	7/11	56° 10.00'	-157° 47.11'	86	8.0	343	17	200	24	0	310	0
5139	7/11	56° 09.88'	-158° 03.96'	41	8.0	616	26	377	55	0	220	0
5140	7/11	56° 20.01'	-158° 04.03'	42	8.0	1,368	56	259	34	0	215	5
5141	6/17	54° 30.01'	-159° 00.42'	148	8.0	180	14	368	46	64	10	5
5142	6/17	54° 29.98'	-159° 17.41'	80	7.9	50	4	298	42	10	196	0
5143	6/19	54° 29.97'	-159° 34.03'	63	7.9	2,129	145	1,043	117	0	142	5
5144	6/18	54° 29.98'	-159° 50.89'	66	7.8	419	30	527	77	0	97	0
5145	6/18	54° 30.00'	-160° 08.93'	67	7.8	1,163	87	1,120	147	0	126	0
5146	6/5	54° 40.02'	-158° 25.05'	121	7.9	864	60	474	58	69	64	10
5147	6/16	54° 39.97'	-158° 42.06'	57	7.9	1,230	84	773	94	0	368	25

<sup>1</sup> Standard skate = 1,800' groundline with 16/0 circle hooks spaced every 18' on 24"-42" gangions.

<sup>2</sup> Weights are calculated from length-weight tables.

<sup>3</sup> Bycatch numbers extrapolated from 20% subsample.

# 2010 IPHC Stock Assessment Survey

## Area 3B

Station	Date Fished	North Latitude	West Longitude	Depth (F)	Skates Set <sup>1</sup>	Legal Halibut		Sublegal Halibut		Bycatch (numbers) <sup>3</sup>		
						Lbs. <sup>2</sup>	#s	Lbs. <sup>2</sup>	#s	Sablefish	P. Cod	Rockfish
5148	6/16	54° 40.02'	-159° 00.18'	50	8.0	1,817	109	585	72	0	277	0
5149	6/17	54° 40.02'	-159° 16.95'	41	7.9	1,125	59	514	74	0	255	0
5150	6/19	54° 40.00'	-159° 34.18'	35	7.9	1,169	53	510	69	0	216	10
5151	6/19	54° 40.02'	-159° 52.11'	42	8.0	1,356	71	651	82	0	252	0
5152	6/12	54° 40.27'	-160° 08.98'	49	7.8	1,438	77	989	126	0	121	0
5153	6/5	54° 49.99'	-158° 07.36'	63	8.0	687	46	1,034	142	5	84	0
5154	6/5	54° 49.95'	-158° 25.03'	108	8.0	894	58	457	56	70	100	0
5155	6/16	54° 50.01'	-158° 42.13'	56	7.8	1,810	107	1,055	148	0	155	0
5156	6/13	54° 49.89'	-159° 00.01'	39	7.8	159	5	149	23	0	262	0
5157	6/12	54° 49.96'	-159° 51.94'	30	8.0	347	14	182	30	0	332	0
5158	6/12	54° 50.00'	-160° 09.28'	38	8.0	543	24	258	39	0	183	0
5159	6/11	54° 50.13'	-160° 26.02'	46	8.0	268	17	357	52	0	134	0
5160	6/6	54° 59.78'	-158° 24.99'	114	8.0	940	59	285	34	104	20	5
5161	6/6	54° 59.99'	-158° 41.96'	70	8.0	1,084	69	1,163	160	0	84	0
5162	6/13	55° 00.00'	-158° 59.14'	46	8.0	243	11	298	53	0	332	0
5163	6/13	54° 59.50'	-159° 16.30'	25	8.0	674	21	33	5	0	371	0
5164	6/11	54° 59.93'	-160° 27.01'	61	7.9	729	44	659	88	0	73	0
5165	6/11	54° 59.90'	-160° 44.00'	47	7.9	1,128	57	802	118	0	113	0
5166	6/6	55° 09.95'	-158° 24.02'	101	7.9	981	66	624	80	5	15	0
5167	6/4	55° 09.97'	-158° 42.12'	113	8.0	1,210	75	267	33	10	104	0
5168	6/4	55° 09.86'	-158° 59.01'	74	8.0	918	63	1,087	144	0	79	0
5169	6/7	55° 09.99'	-159° 16.88'	40	7.9	560	27	198	28	0	372	0
5170	6/1	55° 19.99'	-158° 41.73'	103	7.9	839	51	128	18	15	103	0
5171	6/4	55° 19.88'	-158° 58.97'	102	8.0	1,608	81	315	37	5	98	0
5172	6/7	55° 19.84'	-159° 17.02'	97	7.9	2,520	151	600	72	5	15	0
5173	6/7	55° 19.98'	-159° 34.05'	76	7.9	1,277	82	1,171	145	0	103	0
5174	5/31	55° 20.03'	-159° 52.03'	45	7.9	678	35	533	80	0	176	0
5175	6/1	55° 29.98'	-158° 40.80'	89	8.0	543	27	171	21	0	30	0
5176	6/1	55° 29.97'	-158° 59.12'	60	8.0	378	24	801	127	0	79	0
5177	6/3	55° 29.61'	-159° 16.98'	70	7.9	692	47	605	83	0	49	0
5178	6/3	55° 29.95'	-159° 35.13'	92	8.0	1,002	54	317	40	0	89	0
5179	5/31	55° 30.16'	-159° 51.95'	93	7.9	969	51	775	103	0	127	0
5181	6/2	55° 40.04'	-158° 59.01'	84	7.9	751	43	402	51	0	191	0
5182	6/3	55° 39.93'	-159° 16.97'	57	8.0	635	38	536	82	0	168	0
5183	5/31	55° 39.98'	-159° 52.42'	72	7.9	1,055	54	347	47	0	145	0
5184	6/2	55° 49.97'	-158° 59.01'	69	7.9	859	54	257	35	0	157	0
5185	6/2	55° 49.98'	-159° 16.96'	34	8.0	591	34	332	43	0	282	0
5186	6/27	53° 59.99'	-163° 14.95'	47	7.9	479	35	645	80	0	172	0
5187	6/27	53° 59.99'	-163° 31.79'	56	7.8	108	8	196	30	0	82	0
5188	6/27	54° 00.01'	-163° 49.11'	51	7.9	118	5	266	46	0	142	0
5189	6/25	54° 09.96'	-161° 34.10'	73	7.9	252	18	236	31	49	118	0
5190	6/25	54° 08.77'	-161° 51.00'	46	7.9	2,433	146	709	84	0	137	5
5191	6/26	54° 09.95'	-162° 07.95'	46	7.8	2,008	113	608	73	0	228	10
5192	6/26	54° 10.02'	-162° 25.28'	83	7.9	97	7	263	36	10	83	15
5193	7/31	54° 10.01'	-163° 50.11'	50	8.0	216	15	785	130	0	69	0
5194	6/18	54° 19.99'	-160° 08.32'	175	7.9	101	8	82	10	59	0	10
5195	6/24	54° 19.95'	-160° 26.27'	68	8.0	488	29	702	106	0	243	0
5196	6/24	54° 20.00'	-160° 43.21'	58	7.9	411	28	348	47	0	230	10
5197	8/10	54° 19.95'	-161° 00.00'	71	8.0	401	28	393	61	0	153	0

<sup>1</sup> Standard skate = 1,800' groundline with 16/0 circle hooks spaced every 18' on 24"-42" gangions.

<sup>2</sup> Weights are calculated from length-weight tables.

<sup>3</sup> Bycatch numbers extrapolated from 20% subsample.

# 2010 IPHC Stock Assessment Survey

## Area 3B

Station	Date Fished	North Latitude	West Longitude	Depth (F)	Skates Set <sup>1</sup>	Legal Halibut		Sublegal Halibut		Bycatch (numbers) <sup>3</sup>		
						Lbs. <sup>2</sup>	#'s	Lbs. <sup>2</sup>	#'s	Sablefish	P. Cod	Rockfish
5198	8/9	54° 19.96'	-161° 17.14'	58	8.0	1,291	86	876	120	0	200	60
5199	8/9	54° 19.99'	-161° 33.98'	78	8.0	595	40	499	70	40	89	0
5200	6/25	54° 20.00'	-161° 51.01'	39	7.9	1,188	62	465	69	0	103	0
5201	6/26	54° 19.69'	-162° 09.00'	33	7.9	1,006	37	60	9	0	83	0
5202	8/3	54° 20.10'	-163° 16.99'	28	8.0	1,650	86	544	72	0	45	0
5203	8/1	54° 20.00'	-163° 34.45'	61	8.0	377	28	802	108	0	168	0
5204	8/1	54° 19.98'	-163° 51.36'	62	8.0	508	36	789	110	0	40	0
5205	8/1	54° 20.00'	-164° 09.12'	51	8.0	197	14	985	149	0	119	0
5206	6/24	54° 29.99'	-160° 26.27'	81	7.8	461	33	724	92	5	126	0
5207	8/10	54° 30.01'	-160° 43.12'	76	8.0	11	1	120	16	10	0	0
5208	8/10	54° 30.01'	-160° 59.88'	71	8.0	192	14	730	111	60	75	0
5209	8/9	54° 29.99'	-161° 17.92'	65	8.0	288	20	1,018	158	25	35	0
5210	8/7	54° 30.01'	-161° 35.00'	36	8.0	508	27	1,024	169	0	145	0
5211	8/7	54° 30.00'	-161° 51.88'	77	8.0	272	20	279	38	5	15	0
5212	8/8	54° 30.01'	-162° 08.62'	77	8.0	526	39	711	94	0	64	0
5213	8/8	54° 30.02'	-162° 25.88'	79	8.0	933	62	1,077	142	0	64	0
5214	8/3	54° 30.07'	-163° 17.99'	41	8.1	1,138	75	1,605	222	0	66	0
5215	8/3	54° 30.09'	-163° 35.00'	54	7.9	336	24	1,016	138	0	49	0
5216	8/2	54° 30.02'	-163° 52.84'	51	8.0	707	54	1,779	240	0	10	0
5217	8/2	54° 30.01'	-164° 10.00'	54	8.0	611	43	1,846	257	0	75	0
5218	6/23	54° 40.11'	-160° 26.00'	56	7.9	1,041	66	1,149	159	0	88	0
5219	6/23	54° 39.98'	-160° 43.02'	53	7.9	601	37	864	128	0	170	0
5220	8/12	54° 40.00'	-161° 00.94'	51	8.0	496	30	855	127	0	150	0
5221	8/12	54° 39.94'	-161° 17.76'	76	8.0	318	24	913	129	5	64	0
5222	8/11	54° 39.98'	-161° 35.02'	35	8.0	317	17	588	93	0	185	0
5223	8/7	54° 40.03'	-161° 53.20'	44	8.0	678	41	1,050	160	0	74	45
5224	8/6	54° 40.02'	-162° 44.00'	47	8.0	393	26	925	133	0	5	0
5225	6/23	54° 49.95'	-160° 43.99'	55	7.9	289	20	626	88	0	147	0
5226	8/12	54° 50.00'	-161° 00.82'	56	8.0	132	9	1,235	190	0	15	0
5227	8/11	54° 49.99'	-161° 18.06'	58	8.0	509	28	1,208	181	0	20	0
5228	8/11	54° 50.02'	-161° 35.96'	44	8.0	835	30	492	73	0	45	0
5229	8/6	54° 50.01'	-162° 44.98'	25	8.0	908	46	682	97	0	180	0
5230	8/6	54° 50.00'	-163° 02.92'	44	8.0	542	31	396	50	0	100	0
5231	6/22	55° 00.01'	-161° 01.31'	57	7.9	776	30	460	66	0	69	0
5232	6/22	55° 00.00'	-161° 19.00'	47	7.9	758	39	612	88	0	125	0
5233	6/22	55° 10.01'	-161° 02.03'	74	7.9	478	25	521	75	0	216	0
5234	6/6	55° 20.00'	-156° 03.24'	152	8.0	1,917	133	477	53	91	40	15
5235	6/6	55° 19.99'	-156° 20.79'	95	8.0	973	61	567	74	25	45	0
5236	6/5	55° 30.12'	-155° 44.99'	120	8.0	184	14	307	44	10	70	5
5237	6/5	55° 29.98'	-156° 02.96'	112	8.0	249	16	243	36	40	55	5
5238	6/7	55° 30.02'	-156° 20.02'	118	8.0	1,166	75	356	43	25	75	0
5239	6/4	55° 40.16'	-155° 25.96'	99	8.0	338	22	322	45	0	69	0
5240	6/5	55° 40.01'	-155° 44.05'	68	8.0	626	39	739	103	0	189	0
5241	6/8	55° 40.15'	-156° 02.02'	125	8.0	864	50	300	39	60	80	0
5242	6/8	55° 40.02'	-156° 18.80'	139	8.0	360	19	134	17	115	40	0
5243	6/7	55° 39.97'	-156° 37.00'	132	8.0	1,559	101	551	71	40	0	5
5244	6/4	55° 50.01'	-155° 07.04'	65	8.0	511	35	770	112	0	21	0
5245	6/4	55° 50.00'	-155° 24.89'	27	8.0	332	21	568	85	0	139	0
5246	6/9	55° 50.01'	-156° 01.05'	59	8.0	828	56	848	111	0	120	0

<sup>1</sup> Standard skate = 1,800' groundline with 16/0 circle hooks spaced every 18' on 24"-42" gangions.

<sup>2</sup> Weights are calculated from length-weight tables.

<sup>3</sup> Bycatch numbers extrapolated from 20% subsample.

# 2010 IPHC Stock Assessment Survey

## Area 3B

Station	Date Fished	North Latitude	West Longitude	Depth (F)	Skates Set <sup>1</sup>	Legal Halibut		Sublegal Halibut		Bycatch (numbers) <sup>3</sup>			
						Lbs. <sup>2</sup>	#s	Lbs. <sup>2</sup>	#s	Sablefish	P. Cod	Rockfish	
5247	6/8	55° 49.95'	-156° 18.95'	131	8.0	335	17	69	9	95	65	0	
5248	6/22	55° 50.12'	-156° 36.00'	125	8.0	896	56	329	43	30	45	0	
5249	7/16	55° 50.09'	-156° 54.00'	73	8.0	1,101	77	1,000	133	0	158	0	
5250	6/9	56° 00.05'	-155° 42.01'	25	8.0	415	31	615	88	0	210	0	
5251	6/9	55° 59.94'	-155° 59.97'	41	8.0	406	28	812	124	0	217	0	
5252	6/22	55° 59.99'	-156° 17.70'	115	8.0	675	37	144	17	115	190	0	
5253	6/22	55° 59.89'	-156° 34.99'	106	8.0	1,647	86	354	43	0	140	0	
5254	7/14	56° 00.03'	-157° 11.03'	61	8.0	308	19	539	90	0	85	0	
5255	7/20	56° 10.09'	-155° 58.95'	116	8.0	453	32	183	23	20	69	5	
5256	7/20	56° 10.00'	-156° 17.00'	127	8.0	436	26	132	15	89	149	0	
5257	7/19	56° 09.52'	-156° 34.98'	103	7.5	432	28	478	65	5	46	0	
5258	7/16	56° 10.00'	-156° 52.94'	44	8.0	297	15	371	59	0	149	0	
5259	7/15	56° 09.98'	-157° 11.01'	56	8.0	733	39	677	98	0	225	0	
5260	7/15	56° 09.84'	-157° 29.02'	85	8.0	407	30	508	65	0	262	0	
5261	7/20	56° 19.99'	-155° 57.99'	114	8.0	587	41	421	51	65	20	5	
5262	7/19	56° 19.98'	-156° 16.02'	153	8.0	207	11	70	9	104	30	0	
5263	7/19	56° 20.00'	-156° 33.91'	102	8.0	1,384	76	523	65	35	79	0	
5264	6/16	56° 19.96'	-156° 52.02'	64	8.0	1,244	49	611	88	0	64	0	
5265	6/16	56° 20.25'	-157° 10.00'	95	8.0	974	48	131	16	0	275	0	
5266	6/15	56° 19.95'	-157° 28.00'	36	8.0	1,688	83	705	98	0	25	0	
5267	6/15	56° 20.00'	-157° 45.98'	30	8.0	971	45	674	97	0	75	0	
5268	6/18	56° 30.02'	-155° 57.23'	136	8.0	431	27	216	27	25	55	0	
5269	6/18	56° 29.94'	-156° 15.00'	142	8.0	444	27	144	19	135	70	0	
5270	6/17	56° 29.98'	-156° 32.99'	107	8.0	719	45	290	38	5	65	0	
5271	6/16	56° 29.79'	-156° 50.98'	51	8.0	328	17	662	95	0	190	0	
5272	6/15	56° 29.99'	-157° 28.12'	89	8.0	613	27	142	18	0	235	0	
5273	6/18	56° 40.00'	-156° 13.87'	118	8.0	949	52	203	23	70	145	0	
5274	6/17	56° 40.00'	-156° 31.97'	86	8.0	746	41	671	88	0	125	0	
5275	6/17	56° 40.10'	-156° 51.00'	54	8.0	1,119	60	1,107	152	0	190	0	
5276	6/14	56° 40.02'	-157° 08.99'	76	8.0	827	40	304	42	0	135	0	
5277	6/13	56° 50.01'	-156° 13.02'	105	8.0	1,354	76	688	91	0	60	0	
5278	6/13	56° 50.00'	-156° 32.02'	60	8.0	974	45	555	80	0	185	0	
5279	6/14	56° 49.93'	-156° 50.02'	61	8.0	520	33	610	80	0	100	0	
5280	6/13	56° 59.98'	-156° 13.11'	82	8.0	585	27	304	44	5	140	0	
<b>230 Total Effective 3B Stations</b>						<b>Totals</b>	<b>167,779</b>	<b>9,948</b>	<b>139,226</b>	<b>19,452</b>	<b>3,871</b>	<b>27,896</b>	<b>333</b>

<sup>1</sup> Standard skate = 1,800' groundline with 16/0 circle hooks spaced every 18' on 24"-42" gangions.

<sup>2</sup> Weights are calculated from length-weight tables.

<sup>3</sup> Bycatch numbers extrapolated from 20% subsample.