

# 2007 IPHC Stock Assessment Survey

## Area 3B

Station	Date Fished	North Latitude	West Longitude	Depth (F)	Skates Set <sup>1</sup>	Legal Halibut		Sublegal Halibut		Bycatch (numbers) <sup>3</sup>		
						Lbs. <sup>2</sup>	#'s	Lbs. <sup>2</sup>	#'s	Sablefish	P. Cod	Rockfish
5001	8/7	56° 00.17'	-153° 35.55'	51	5.0	1,515	65	675	103	0	0	0
5002	8/7	56° 00.03'	-153° 54.09'	44	5.0	1,965	81	204	32	0	0	0
5003	7/23	56° 00.38'	-154° 13.96'	60	5.0	734	45	545	78	0	37	0
5004	7/23	56° 00.47'	-154° 30.15'	179	5.0	806	56	237	33	0	55	0
5005	7/22	56° 00.00'	-154° 47.90'	113	5.0	415	26	305	37	29	38	0
5006	7/22	56° 00.36'	-155° 06.17'	29	5.0	420	30	792	102	0	188	0
5007	8/7	56° 10.57'	-153° 36.84'	76	5.0	1,033	57	183	23	0	105	0
5008	8/7	56° 09.93'	-153° 52.61'	124	5.0	3,002	188	215	23	5	0	15
5009	7/23	56° 10.02'	-154° 10.96'	62	5.0	1,972	111	657	87	0	20	0
5010	7/23	56° 09.97'	-154° 28.85'	50	5.0	1,874	100	648	80	0	0	5
5011	7/22	56° 09.91'	-154° 47.27'	44	5.0	365	24	608	83	0	40	0
5013	7/21	56° 10.18'	-155° 24.01'	20	5.0	739	43	441	56	0	0	0
5014	7/21	56° 10.54'	-155° 41.44'	31	5.1	614	29	359	51	0	30	0
5015	7/24	56° 19.93'	-153° 52.01'	47	5.0	591	26	168	23	0	20	0
5016	7/24	56° 20.13'	-154° 10.46'	49	5.0	521	31	210	28	0	100	0
5017	7/24	56° 19.95'	-154° 27.66'	34	5.0	836	35	123	18	0	34	0
5018	7/21	56° 19.84'	-155° 21.24'	23	5.0	385	23	807	105	0	5	0
5019	7/21	56° 19.79'	-155° 39.90'	37	5.0	359	16	186	34	0	50	0
5020	7/20	56° 30.06'	-155° 20.99'	29	5.0	217	13	490	70	0	5	0
5021	8/6	56° 30.22'	-155° 38.37'	60	5.0	804	47	257	34	0	108	0
5022	7/20	56° 39.75'	-155° 01.46'	21	5.0	739	30	187	24	0	5	0
5023	7/20	56° 39.77'	-155° 19.51'	49	5.1	854	38	154	20	0	40	0
5024	8/6	56° 40.08'	-155° 37.80'	130	5.0	433	26	68	7	101	10	0
5025	8/6	56° 40.05'	-155° 55.22'	152	5.0	354	18	54	6	87	5	0
5026	7/19	56° 49.94'	-154° 24.23'	33	5.0	1,065	50	413	50	0	85	0
5027	7/19	56° 49.99'	-154° 42.16'	24	5.0	694	43	399	53	0	0	0
5028	7/31	56° 50.08'	-155° 00.65'	41	5.0	1,548	64	453	70	0	30	0
5029	7/31	56° 49.94'	-155° 17.87'	119	5.0	1,426	79	281	33	40	10	0
5030	8/5	56° 50.20'	-155° 36.55'	151	5.0	839	48	56	7	65	5	0
5031	8/5	56° 50.25'	-155° 54.11'	161	5.0	1,094	48	30	3	94	10	5
5032	7/19	56° 59.90'	-154° 41.18'	23	4.9	1,172	40	306	40	0	5	0
5033	7/31	56° 59.97'	-154° 59.70'	67	5.0	981	49	334	49	0	30	0
5034	7/31	56° 59.59'	-155° 17.77'	134	5.0	555	35	80	9	50	0	0
5035	8/5	57° 00.02'	-155° 36.83'	158	5.0	656	36	85	10	90	0	0
5036	8/5	56° 59.95'	-155° 53.72'	147	5.0	273	12	0	0	74	134	0
5037	7/27	57° 09.53'	-154° 40.36'	32	5.0	854	39	345	47	0	20	0
5038	7/27	57° 10.01'	-154° 57.91'	105	5.0	686	37	96	13	5	75	0
5039	7/30	57° 09.57'	-155° 16.45'	135	5.0	931	55	191	22	100	0	0
5040	7/30	57° 10.04'	-155° 34.91'	143	5.0	555	31	84	10	70	5	0
5041	7/28	57° 09.75'	-155° 52.84'	144	5.0	328	16	76	9	54	225	0
5042	7/27	57° 20.00'	-154° 58.09'	114	5.0	265	13	30	4	20	130	0
5043	7/30	57° 19.76'	-155° 15.07'	133	5.0	1,047	53	120	14	25	15	0
5044	7/28	57° 20.21'	-155° 33.71'	155	5.0	1,018	55	145	18	35	5	0
5045	7/29	57° 19.70'	-155° 52.23'	55	5.0	1,390	70	345	49	90	0	0
5046	7/29	57° 20.27'	-156° 10.60'	88	5.0	614	19	33	4	0	49	0
5047	7/28	57° 29.78'	-155° 14.56'	142	5.0	1,616	71	142	17	40	5	0
5048	7/28	57° 29.99'	-155° 32.34'	165	5.0	649	38	213	24	24	0	0
5096	6/9	54° 50.25'	-157° 33.02'	228	5.0	201	13	0	0	163	0	0
5097	6/10	54° 50.05'	-157° 50.05'	95	4.9	393	26	381	50	0	39	0
5098	6/9	55° 00.00'	-157° 15.28'	100	4.8	271	21	283	34	14	72	0

<sup>1</sup> Standard skate = 1,800' groundline with 16/0 circle hooks spaced every 18' on 24"-42" gangions.

<sup>2</sup> Weights are calculated from length-weight tables.

<sup>3</sup> Bycatch numbers extrapolated from 20% subsample.

# 2007 IPHC Stock Assessment Survey

## Area 3B

Station	Date Fished	North Latitude	West Longitude	Depth (F)	Skates Set <sup>1</sup>	Legal Halibut		Sublegal Halibut		Bycatch (numbers) <sup>3</sup>		
						Lbs. <sup>2</sup>	#s	Lbs. <sup>2</sup>	#s	Sablefish	P. Cod	Rockfish
5099	6/9	55° 00.01'	-157° 31.94'	55	5.0	2,649	164	373	46	0	139	5
5100	6/10	54° 59.99'	-157° 49.97'	45	5.0	2,098	88	304	41	0	149	0
5101	6/10	55° 00.00'	-158° 07.01'	74	5.0	708	42	488	73	0	25	0
5102	6/7	55° 10.02'	-156° 22.35'	277	5.0	0	0	0	0	94	0	0
5103	6/7	55° 10.00'	-156° 38.78'	292	5.0	0	0	0	0	140	0	0
5104	6/8	55° 09.99'	-156° 57.21'	84	4.9	327	21	155	16	0	279	0
5105	6/8	55° 10.02'	-157° 13.88'	62	4.9	1,417	90	379	54	0	54	0
5106	6/17	55° 09.96'	-157° 32.01'	47	5.0	1,820	103	956	129	0	15	0
5107	6/17	55° 10.00'	-157° 48.86'	43	5.0	1,453	66	1,125	170	0	0	0
5108	6/18	55° 10.00'	-158° 07.22'	56	5.0	1,968	88	272	39	0	193	0
5109	6/7	55° 19.99'	-156° 39.18'	63	4.9	1,051	65	751	105	0	108	0
5110	6/8	55° 19.69'	-156° 55.98'	52	5.0	1,207	75	859	125	0	140	0
5111	6/16	55° 20.14'	-157° 14.02'	49	4.9	1,009	55	716	108	0	83	0
5112	6/17	55° 20.00'	-157° 30.80'	48	4.9	652	33	455	71	0	129	0
5113	6/18	55° 20.00'	-157° 49.22'	45	5.0	1,628	66	771	121	0	0	0
5114	6/18	55° 20.00'	-158° 06.15'	59	4.9	818	43	576	88	0	10	0
5115	6/27	55° 20.00'	-158° 23.99'	81	5.0	543	32	218	29	25	40	0
5116	6/6	55° 29.98'	-156° 38.23'	99	5.0	1,066	64	178	22	15	130	0
5117	6/6	55° 29.91'	-156° 55.02'	50	5.0	2,066	105	575	77	0	147	0
5118	6/16	55° 30.09'	-157° 13.01'	48	5.0	1,629	87	877	119	0	59	0
5119	6/16	55° 30.00'	-157° 31.27'	52	5.0	642	29	339	50	0	0	0
5120	6/19	55° 30.00'	-157° 48.00'	55	5.0	484	31	661	104	0	30	0
5121	6/19	55° 30.05'	-158° 06.00'	71	5.0	570	34	697	103	10	90	0
5122	6/27	55° 30.00'	-158° 23.95'	79	5.0	497	33	358	49	10	70	0
5123	6/6	55° 40.12'	-156° 55.00'	50	5.0	542	28	1,107	173	0	25	0
5124	6/15	55° 39.97'	-157° 13.01'	46	5.0	566	22	426	72	0	5	0
5125	6/15	55° 40.00'	-157° 30.09'	54	4.9	1,161	65	824	113	0	25	0
5126	6/19	55° 40.00'	-157° 47.95'	74	5.0	832	58	599	76	15	69	0
5127	6/23	55° 40.00'	-158° 06.10'	71	5.0	1,267	67	774	103	0	149	0
5128	6/23	55° 40.00'	-158° 23.01'	73	5.0	898	61	1,152	144	0	80	0
5129	6/26	55° 40.00'	-158° 41.01'	48	5.0	779	35	1,014	156	0	5	0
5130	6/15	55° 49.63'	-157° 12.05'	55	5.0	439	33	648	89	0	145	0
5131	6/14	55° 50.05'	-157° 29.99'	56	5.0	740	43	1,385	185	0	20	0
5132	6/14	55° 50.00'	-157° 47.98'	66	5.0	723	51	981	142	0	79	0
5133	6/25	55° 50.00'	-158° 04.94'	43	5.0	560	29	1,063	167	0	0	0
5134	6/23	55° 50.00'	-158° 22.94'	59	5.0	573	28	667	97	0	89	0
5135	6/14	55° 59.97'	-157° 29.00'	61	5.0	967	53	719	94	0	35	0
5136	6/25	55° 59.99'	-157° 47.11'	67	5.0	412	27	436	61	0	25	0
5137	6/25	56° 00.01'	-158° 05.04'	44	5.0	977	37	431	60	0	0	0
5138	6/24	56° 10.00'	-157° 47.22'	80	5.0	1,758	70	267	35	0	134	0
5139	6/24	56° 10.07'	-158° 04.93'	31	5.0	1,140	54	283	37	0	30	0
5140	6/24	56° 20.00'	-158° 03.70'	36	5.0	742	36	252	30	0	0	0
5141	7/9	54° 30.11'	-159° 00.00'	151	4.9	381	25	126	14	103	0	0
5142	7/9	54° 29.99'	-159° 17.00'	79	5.0	337	24	191	25	0	141	0
5143	7/10	54° 30.05'	-159° 34.00'	62	5.0	3,268	183	562	68	0	25	0
5144	7/11	54° 30.01'	-159° 51.06'	65	5.0	221	16	327	50	0	223	0
5145	7/11	54° 30.01'	-160° 09.00'	66	5.0	379	27	646	91	0	50	0
5146	7/8	54° 40.00'	-158° 25.00'	114	5.0	2,118	137	518	62	15	45	0
5147	7/8	54° 39.99'	-158° 42.01'	57	5.0	787	51	314	39	0	262	5
5148	7/9	54° 40.02'	-158° 59.50'	49	5.0	1,399	75	604	83	0	105	0

<sup>1</sup> Standard skate = 1,800' groundline with 16/0 circle hooks spaced every 18' on 24"-42" gangions.

<sup>2</sup> Weights are calculated from length-weight tables.

<sup>3</sup> Bycatch numbers extrapolated from 20% subsample.

# 2007 IPHC Stock Assessment Survey

## Area 3B

Station	Date Fished	North Latitude	West Longitude	Depth (F)	Skates Set <sup>1</sup>	Legal Halibut		Sublegal Halibut		Bycatch (numbers) <sup>3</sup>		
						Lbs. <sup>2</sup>	#'s	Lbs. <sup>2</sup>	#'s	Sablefish	P. Cod	Rockfish
5149	7/10	54° 40.01'	-159° 16.95'	39	5.0	1,686	93	849	121	0	15	0
5150	7/10	54° 39.51'	-159° 32.36'	37	5.0	1,455	64	682	101	0	30	5
5151	7/11	54° 40.03'	-159° 52.00'	41	5.0	2,262	109	783	103	0	5	0
5152	7/12	54° 40.00'	-160° 09.04'	49	5.0	1,496	101	758	99	0	125	0
5153	6/11	54° 50.00'	-158° 06.92'	58	5.0	1,766	113	647	91	0	30	0
5154	6/11	54° 50.02'	-158° 24.80'	109	4.9	810	52	188	23	83	0	5
5155	7/8	54° 50.04'	-158° 41.98'	55	5.0	1,861	100	768	115	0	94	0
5156	6/30	54° 50.02'	-159° 00.16'	39	5.0	555	33	524	94	0	10	0
5157	7/12	54° 50.00'	-159° 52.06'	30	4.9	619	17	440	69	0	107	0
5158	7/12	54° 49.89'	-160° 09.02'	38	5.0	1,718	68	767	121	0	0	0
5159	7/13	54° 49.94'	-160° 26.00'	46	5.0	417	28	307	42	0	135	0
5160	6/11	54° 59.97'	-158° 25.00'	117	5.0	2,141	125	236	29	85	50	0
5161	6/30	54° 59.84'	-158° 41.98'	68	4.5	1,277	78	678	96	0	98	4
5162	6/30	54° 59.99'	-158° 59.19'	46	5.0	419	22	505	88	0	55	0
5163	7/1	54° 59.61'	-159° 17.00'	23	5.0	1,910	43	149	21	0	5	0
5164	7/13	55° 00.00'	-160° 27.04'	62	5.0	995	71	712	94	0	45	0
5165	7/13	55° 00.00'	-160° 44.06'	49	5.0	850	45	974	144	0	5	0
5166	7/2	55° 09.91'	-158° 24.00'	101	4.0	490	32	214	30	40	0	0
5167	7/2	55° 09.91'	-158° 42.01'	112	5.0	728	37	121	16	25	0	0
5168	7/1	55° 10.00'	-158° 59.05'	76	5.0	2,053	124	593	77	0	15	0
5169	7/1	55° 09.98'	-159° 17.01'	38	5.1	1,580	70	478	62	0	5	0
5170	7/2	55° 20.00'	-158° 41.93'	101	5.0	1,153	69	254	32	35	20	0
5171	7/3	55° 20.02'	-158° 58.98'	103	5.0	1,605	92	551	66	10	15	0
5172	7/3	55° 20.04'	-159° 16.98'	96	5.0	3,209	205	763	85	0	20	0
5173	7/4	55° 20.01'	-159° 33.98'	77	4.9	935	64	438	53	0	34	0
5174	7/4	55° 19.99'	-159° 52.24'	46	5.0	718	34	546	80	0	0	0
5175	6/27	55° 30.00'	-158° 40.98'	89	5.0	545	23	346	47	10	0	0
5176	6/26	55° 30.05'	-158° 59.02'	61	4.9	591	35	933	131	0	15	0
5177	7/3	55° 30.00'	-159° 17.19'	66	5.0	789	45	649	89	0	145	0
5178	7/5	55° 29.90'	-159° 34.01'	93	4.9	1,454	74	386	47	0	15	0
5179	7/5	55° 30.02'	-159° 52.02'	92	5.0	1,160	65	228	26	0	45	0
5181	6/26	55° 40.00'	-158° 59.05'	83	5.0	1,684	91	266	30	0	45	0
5182	6/22	55° 39.97'	-159° 16.99'	59	5.0	277	19	312	42	0	40	0
5183	7/5	55° 40.00'	-159° 51.95'	71	5.0	1,215	66	378	47	0	130	0
5184	6/22	55° 50.02'	-158° 58.99'	69	5.0	1,803	88	569	74	0	95	0
5185	6/22	55° 50.05'	-159° 17.00'	29	5.0	803	40	351	46	0	45	0
5186	7/26	54° 00.00'	-163° 15.16'	46	5.0	452	30	263	38	0	54	5
5187	7/26	54° 00.00'	-163° 31.98'	56	5.0	50	4	167	31	0	158	0
5188	7/26	53° 59.99'	-163° 49.00'	51	5.0	42	3	213	36	0	115	0
5189	7/24	54° 10.00'	-161° 34.22'	70	5.0	214	15	494	74	15	55	0
5190	7/24	54° 10.00'	-161° 51.01'	45	5.0	2,589	138	519	66	0	20	15
5191	7/25	54° 10.01'	-162° 08.27'	47	5.0	1,669	99	407	50	0	139	5
5192	7/25	54° 09.97'	-162° 24.98'	95	5.0	736	44	235	31	25	40	10
5193	7/26	54° 09.95'	-163° 49.98'	49	5.0	233	18	358	53	0	25	0
5194	7/22	54° 19.98'	-160° 08.20'	175	5.0	42	2	0	0	70	0	5
5195	7/22	54° 19.82'	-160° 26.00'	70	5.0	582	40	545	76	0	95	0
5196	7/23	54° 20.08'	-160° 42.98'	58	5.1	832	52	245	30	0	242	10
5197	7/23	54° 20.01'	-160° 59.98'	70	5.0	222	15	413	64	0	200	0
5198	7/24	54° 19.98'	-161° 16.97'	59	5.0	1,424	86	487	65	0	104	5
5199	7/24	54° 19.98'	-161° 34.26'	79	5.0	263	14	91	12	65	20	0

<sup>1</sup> Standard skate = 1,800' groundline with 16/0 circle hooks spaced every 18' on 24"-42" gangions.

<sup>2</sup> Weights are calculated from length-weight tables.

<sup>3</sup> Bycatch numbers extrapolated from 20% subsample.

# 2007 IPHC Stock Assessment Survey

## Area 3B

Station	Date Fished	North Latitude	West Longitude	Depth (F)	Skates Set <sup>1</sup>	Legal Halibut		Sublegal Halibut		Bycatch (numbers) <sup>3</sup>		
						Lbs. <sup>2</sup>	#'s	Lbs. <sup>2</sup>	#'s	Sablefish	P. Cod	Rockfish
5200	7/25	54° 19.80'	-161° 51.01'	41	5.0	1,570	88	554	74	0	105	0
5201	7/25	54° 20.07'	-162° 09.04'	31	5.0	865	57	764	100	0	40	0
5202	7/28	54° 20.01'	-163° 17.04'	27	5.0	921	60	731	92	0	60	0
5203	7/28	54° 20.03'	-163° 34.03'	60	5.1	509	37	281	36	20	212	0
5204	7/27	54° 20.02'	-163° 51.22'	62	5.0	463	33	536	71	0	85	0
5205	7/27	54° 20.04'	-164° 08.99'	52	5.0	253	18	263	40	0	140	0
5206	7/22	54° 29.95'	-160° 26.01'	81	5.0	527	37	507	68	0	125	0
5207	7/23	54° 30.00'	-160° 43.13'	77	5.0	377	29	853	110	0	50	0
5208	7/23	54° 30.02'	-161° 00.22'	72	5.0	260	19	456	68	5	134	0
5209	8/4	54° 29.91'	-161° 18.00'	67	5.1	383	26	847	134	0	30	0
5210	8/4	54° 30.02'	-161° 34.97'	36	5.0	514	30	777	112	0	45	0
5211	8/3	54° 29.98'	-161° 52.06'	78	5.0	1,423	91	604	70	0	10	0
5212	8/3	54° 29.99'	-162° 09.14'	78	5.0	976	56	400	48	0	15	0
5213	8/3	54° 30.01'	-162° 26.09'	81	5.0	981	51	379	49	0	119	0
5214	7/28	54° 29.82'	-163° 18.02'	39	5.0	701	43	602	79	0	15	0
5215	7/28	54° 30.12'	-163° 35.00'	54	5.0	286	21	436	64	0	40	0
5216	7/27	54° 29.95'	-163° 53.02'	50	5.0	697	50	527	67	0	54	0
5217	7/27	54° 30.04'	-164° 10.01'	51	5.0	220	15	174	21	0	80	0
5218	7/22	54° 39.82'	-160° 25.98'	56	5.0	1,525	97	640	92	0	89	0
5219	8/6	54° 40.00'	-160° 43.17'	52	5.0	1,454	89	542	76	0	40	0
5220	8/6	54° 40.00'	-161° 01.17'	51	5.0	1,258	82	310	39	0	90	0
5221	8/5	54° 40.03'	-161° 17.99'	74	5.0	667	41	502	69	0	10	0
5222	8/4	54° 40.00'	-161° 34.85'	36	5.0	1,163	54	525	74	0	5	40
5223	8/3	54° 39.73'	-161° 53.02'	32	5.0	1,452	53	672	97	0	5	0
5224	7/29	54° 40.05'	-162° 44.00'	47	5.0	384	24	262	35	0	25	0
5225	8/6	54° 49.98'	-160° 44.00'	55	5.0	492	38	819	108	0	100	0
5226	8/6	54° 50.00'	-161° 01.06'	57	5.0	458	34	1,052	152	0	0	0
5227	8/5	54° 50.02'	-161° 18.07'	59	5.0	586	24	394	57	0	0	0
5228	8/5	54° 50.02'	-161° 35.94'	43	5.0	883	33	308	41	0	59	5
5229	7/29	54° 50.00'	-162° 45.11'	27	5.0	651	32	304	40	0	25	0
5230	7/29	54° 50.02'	-163° 03.15'	45	5.0	1,643	90	608	75	0	40	0
5231	8/7	55° 00.02'	-161° 01.14'	56	5.0	611	29	279	36	0	60	0
5232	8/7	55° 00.01'	-161° 19.08'	45	5.0	569	28	518	73	0	50	0
5233	8/7	55° 10.00'	-161° 01.98'	76	5.0	585	35	287	37	0	50	0
5234	6/5	55° 20.02'	-156° 02.79'	152	5.0	1,713	102	99	10	140	0	5
5235	6/5	55° 19.95'	-156° 21.00'	95	5.0	1,241	80	477	59	5	59	0
5236	6/6	55° 30.03'	-155° 45.08'	120	5.0	2,228	140	563	65	10	0	0
5237	6/6	55° 30.10'	-156° 03.00'	111	5.0	228	16	177	24	30	15	0
5238	6/5	55° 29.86'	-156° 20.10'	119	4.9	727	46	246	32	29	82	0
5239	6/7	55° 40.11'	-155° 26.02'	99	5.0	1,105	70	531	63	0	15	0
5240	6/6	55° 40.05'	-155° 43.92'	69	4.9	1,072	69	619	85	0	49	0
5241	6/6	55° 40.03'	-156° 02.07'	126	5.0	1,263	73	127	17	50	70	0
5242	6/9	55° 40.11'	-156° 19.27'	139	5.0	1,096	53	127	17	59	0	0
5243	6/9	55° 40.02'	-156° 37.03'	131	5.0	829	44	198	24	49	0	0
5244	6/7	55° 50.10'	-155° 06.97'	65	4.9	1,475	88	518	68	0	0	0
5245	6/7	55° 49.88'	-155° 25.03'	26	5.1	641	32	175	24	0	0	0
5246	6/8	55° 49.79'	-156° 01.00'	58	4.9	2,031	108	602	80	0	0	0
5247	6/9	55° 50.00'	-156° 19.07'	132	5.0	1,105	62	103	13	30	0	0
5248	6/9	55° 50.04'	-156° 36.00'	125	4.9	1,188	66	196	23	15	5	0
5249	6/27	55° 50.10'	-156° 53.97'	73	5.0	875	57	333	41	0	69	0

<sup>1</sup> Standard skate = 1,800' groundline with 16/0 circle hooks spaced every 18' on 24"-42" gangions.

<sup>2</sup> Weights are calculated from length-weight tables.

<sup>3</sup> Bycatch numbers extrapolated from 20% subsample.

# 2007 IPHC Stock Assessment Survey

## Area 3B

Station	Date Fished	North Latitude	West Longitude	Depth (F)	Skates Set <sup>1</sup>	Legal Halibut		Sublegal Halibut		Bycatch (numbers) <sup>3</sup>			
						Lbs. <sup>2</sup>	#'s	Lbs. <sup>2</sup>	#'s	Sablefish	P. Cod	Rockfish	
5250	6/8	56° 00.03'	-155° 41.97'	26	4.8	342	23	556	67	115	0	0	
5251	6/8	56° 00.01'	-155° 59.78'	42	4.9	200	12	229	37	0	10	0	
5252	6/15	56° 00.01'	-156° 17.80'	116	4.9	1,672	82	23	3	99	10	0	
5253	6/15	55° 59.99'	-156° 35.25'	106	5.0	1,425	67	85	11	0	25	0	
5254	6/27	56° 00.08'	-157° 11.03'	61	4.9	377	26	410	59	0	74	0	
5255	6/14	56° 10.09'	-155° 58.98'	116	5.0	1,046	60	148	18	45	10	0	
5256	6/14	56° 10.07'	-156° 16.98'	125	4.9	1,026	47	143	17	98	21	0	
5257	6/15	56° 10.01'	-156° 35.01'	100	5.0	1,640	96	349	47	5	20	0	
5258	6/27	56° 10.00'	-156° 53.10'	43	4.9	386	10	128	17	0	64	0	
5259	6/26	56° 10.00'	-157° 10.82'	53	4.9	1,212	54	497	69	0	5	0	
5260	6/26	56° 10.00'	-157° 28.99'	84	5.0	754	42	123	14	0	25	0	
5261	6/14	56° 20.00'	-155° 57.75'	113	4.9	729	41	155	19	73	15	0	
5262	6/14	56° 20.00'	-156° 16.00'	152	4.9	689	35	47	5	64	0	0	
5263	6/25	56° 20.00'	-156° 33.78'	102	5.0	1,269	69	240	30	0	89	0	
5264	6/25	56° 20.00'	-156° 51.80'	65	5.0	837	48	585	82	0	10	0	
5265	6/26	56° 20.02'	-157° 10.00'	95	4.9	1,066	57	96	11	0	89	0	
5266	6/23	56° 20.02'	-157° 27.95'	38	4.9	176	13	256	36	0	0	5	
5267	6/23	56° 19.89'	-157° 45.99'	29	5.0	475	23	164	22	0	5	0	
5268	6/13	56° 30.03'	-155° 57.03'	133	5.0	1,140	62	97	13	59	0	0	
5269	6/13	56° 29.91'	-156° 15.00'	141	5.0	731	41	99	12	50	50	0	
5270	6/25	56° 30.00'	-156° 32.99'	105	5.1	1,276	68	323	39	0	15	0	
5271	6/25	56° 30.06'	-156° 50.99'	52	4.9	233	11	593	86	0	15	0	
5272	6/23	56° 30.23'	-157° 27.98'	80	4.9	2,028	88	292	39	0	5	0	
5273	6/13	56° 40.23'	-156° 14.09'	114	4.9	1,002	55	251	28	29	44	0	
5274	6/12	56° 40.23'	-156° 32.00'	85	4.9	944	52	264	34	0	78	0	
5275	6/24	56° 40.00'	-156° 50.86'	57	4.9	274	13	397	62	0	10	0	
5276	6/24	56° 40.20'	-157° 09.02'	67	5.0	916	47	188	27	0	59	0	
5277	6/12	56° 50.00'	-156° 13.05'	103	4.9	605	32	241	29	5	170	0	
5278	6/12	56° 50.08'	-156° 32.12'	60	4.9	1,145	43	344	56	0	15	0	
5279	6/24	56° 50.12'	-156° 50.00'	62	5.0	1,360	63	332	44	0	55	0	
5280	6/12	57° 00.31'	-156° 12.99'	85	4.8	416	16	98	14	0	86	0	
<b>231 Total Effective 3B Stations</b>						<b>Totals</b>	<b>219,827</b>	<b>12,009</b>	<b>95,234</b>	<b>13,054</b>	<b>3,247</b>	<b>11,698</b>	<b>159</b>

<sup>1</sup> Standard skate =1,800' groundline with 16/0 circle hooks spaced every 18' on 24"-42" gangions.

<sup>2</sup> Weights are calculated from length-weight tables.

<sup>3</sup> Bycatch numbers extrapolated from 20% subsample.